

FIREscape

EL-20

EL-20 Addressable Exit Sign

Features

- ▶ Complies with BS5266
- ▶ Visible at 20 metres
- ▶ LED technology
- ▶ Integral stand-by battery
- ▶ Hinged to fit to any surface angle
- ▶ Fixes easily to standard Hochiki base (YBN-R/3)



Description

A LED-based, addressable 20 m viewable exit light with a flexible 'flex it' hinge solution. The exit light's hinge cup contains the electronics and stand-by battery and allows the unit to attach to the standard Hochiki YBN-R/3 sensor mounting base. The cup also features a bi-coloured status LED indicating charge/fault status (green for charging, red for fault).

Specification

Cup and bar colour	White
Materials	Fire resistant PC + ABS plastic (FR3010) Plexiglass-8N (sign)
Fire class	UL94 V-0
Viewing distance	20 m
Operating Humidity	RH 95% non-condensing
Operating Temperature	-20°C to +40°C
Ingress Protection Rating	IP20
Operation time	1 hour / 3 hour
Dimensions of sign (mm)	202W x 210H x 100D (inc cup)
Distance from wall in wall installation (mm)	75 (inc 8 for YBN-R/3 base)
Drop from ceiling in ceiling installation (mm)	217 (inc 8 for YBN-R/3 base)
Weight including battery (g)	330
Energy Consumption	0.58 W (charging)
	0.50 W (not charging)

Ordering Codes

Product	Part Number
20m Arrow to Left Emergency exit sign	EL-20L
20m Arrow to Right Emergency exit sign	EL-20R
20m Arrow to Down Emergency exit sign	EL-20D
20m Arrow to Up Emergency exit sign	EL-20U

Approvals



Luminaires awarded BSI Kitemark™